

# Fittings & Accessories



<b>630</b> <b>Angle Elbow</b> SWIVEL FEMALE x MALE
• 2 1/2" & 3" sizes in 30° (64 & 76 mm)
• 4" size 45° (102 mm)
† 2 1/2" x 2 1/2" (65 x 65 mm)
3" x 2 1/2" (75 x 65 mm)
3" x 3" (76 x 76 mm)
◊ 4" x 4" (100 x 100 mm)

<b>632</b> <b>90° Suction Elbow</b> FEMALE x MALE
† ◊ 2 1/2" x 2 1/2" (65 x 65 mm)
◊ 4" x 4" (100 x 100 mm)
† 5" x 5" (125 x 125 mm)

<b>655</b> <b>90° Front Suction Elbow with Strainer</b> FEMALE NPT x MALE NH
# 4" x 4" (100 x 100 mm)
# 4" x 4 1/2" (100 x 114 mm)
# ◊ 5" x 5" (125 x 125 mm)
# ◊ 5" x 6" (125 x 150 mm)

<b>635</b> <b>90° Continuous Swiveling Elbow</b> FEMALE NPT x MALE NH or NPSH
• Full 2" (51 mm) waterway with cast-in turning vane
# 1 1/2" 2" or 2" female x 1 1/2" male (38 or 50 x 38 mm)
2 7/16" or 4 5/8" length
# 2 1/2" female x 2 1/2" male (63 mm x 65 mm)
5" length

<b>347</b> <b>Hose Plug</b>
• Available with rocker lug
• Chain optional through 4" (102 mm)
† 1 1/2" (38 mm)
† 2" (50 mm)
† 2 1/2" (65 mm)
† 3" (75 mm)
3 1/2" (89 mm)
† 4" (100 mm)
4 1/2" (114 mm)
5" (125 mm)
6" (150 mm)

<b>KEY</b>
√ Optional with strainer
* Pyrolite
† Cast or chrome
◊ Chrome Ends with Red Paint
# Cast brass

NOTE: All items are chrome, unless noted otherwise.



<b>326</b> <b>British Instantaneous Adapter</b> MALE x BIM
*# 1 1/2" x 2 1/2" (38 x 38 mm)
*# 2 1/2" x 2 1/2" (65 x 65 mm)

<b>335</b> <b>Double Female Swivel Adapter</b>
* † 1 1/2" (38 mm)
† 2" (50 mm)
* † 2 1/2" (65 mm)
3" X 2 1/2" (75 x 38 mm)
† 3" (75 mm)

<b>336</b> <b>Double Male Adapter</b>
* † 1 1/2" (38 mm)
† 2" (50 mm)
* † 2 1/2" (65 mm)
3" X 2 1/2" (75 x 65 mm)
† 3" (75 mm)
4" (100 mm) Pyrolite only

<b>354</b> <b>Female Swivel to Male Adapter</b>
• Long handle or rocker lug
2 1/2" x 2 1/2" (65 x 65 mm)
2 1/2" x 3" (65 x 75 mm)
2 1/2" x 3 1/2" (65 x 89 mm)
2 1/2" x 4" (65 x 100 mm)
2 1/2" x 4 1/2" (65 x 114 mm)
2 1/2" x 5" (65 x 125 mm)
2 1/2" x 6" (65 x 150 mm)
3" x 2 1/2" (75 x 65 mm)
3" x 3" (76 x 76 mm)
3" x 3 1/2" (75 x 89 mm)
3" x 4" (75 x 100 mm)
3" x 4 1/2" (75 x 114 mm)
3 1/2" x 2 1/2" (89 x 89 mm)
3 1/2" x 3" (89 x 75 mm)
3 1/2" x 4 1/2" (89 x 114 mm)
4" x 2 1/2" (100 x 64 mm)
4" x 3" (100 x 75 mm)
4" x 4 1/2" (100 x 114 mm)
4" x 5" (100 x 125 mm)
4" x 6" (100 x 153 mm)
4 1/2" x 2 1/2" (114 x 65 mm)
4 1/2" x 4" (114 x 100 mm)
4 1/2" x 4 1/2" (114 x 114 mm)
4 1/2" x 5" (114 x 125 mm)
4 1/2" x 6" (114 x 150 mm)
5" x 4" (125 x 100 mm)
5" x 4 1/2" (125 x 114 mm)
5" x 6" (125 x 150 mm)
6" x 2 1/2" (150 x 65 mm)
6" x 4" (150 x 100 mm)
6" x 4 1/2" (150 x 114 mm)
6" x 5" (150 x 127 mm)

<b>357</b> <b>Double Female Swivel Adapter</b>
• Long handle or rocker lug
3 1/2" x 3 1/2" (89 x 89 mm)
4" x 2 1/2" (100 x 65 mm)
4" x 3 1/2" (100 x 89 mm)
* 4" x 4" (100 x 100 mm)
* 4 1/2" x 2 1/2" (114 x 114 mm)
4 1/2" x 3" (114 x 75 mm)
4 1/2" x 4" (114 x 100 mm)
* 4 1/2" x 4 1/2" (114 x 114 mm)
* 5" x 2 1/2" (125 x 65 mm)
* 5" x 4" (125 x 100 mm)
* 5" x 4 1/2" (125 x 114 mm)
5" x 5" (125 x 125 mm)
* 6" x 2 1/2" (150 x 65 mm)
6" x 3 1/2" (150 x 89 mm)
6" x 4" (150 x 100 mm)
* 6" x 4 1/2" (150 x 114 mm)
* 6" x 5" (150 x 125 mm)
* 6" x 6" (150 x 150 mm)

- 1422 Rigid Direct Connect Base**
- For adapting an 1 1/2" nozzle base to a 2 1/2" hose line
  - Pyrolite® construction
  - 2 1/2" female x 1 1/2" male
  - Tapered waterway for reduced turbulence
  - Weight: 12 oz.



Style 1422

- 422 Rigid Direct Connect Base**
- Same as Style 1422 except brass with cast or chrome finish
  - Weight: 1 1/2 lbs.



<b>345</b> <b>Hose Cap</b>
• Available with rocker lug
• 2" and 3" (51 & 76 mm) available with long handle
• Chain optional
† 3/4" GHT (19 mm)
† 1" (25 mm)
† 1 1/2" (38 mm)
† 2" (50 mm)
† 2 1/2" (65 mm)
† 3" (75 mm)
† 3 1/2" (89 mm)



**KEY**

- ✓ Optional with strainer
- \* Pyrolite
- † Cast or chrome
- ◇ Chrome Ends with Red Paint
- # Cast brass

NOTE: All items are chrome, unless noted otherwise.



**331**  
**Long Internal Lug Adapter**  
 FEMALE NPT x MALE  
 † 2 1/2" only (65 mm)



**330**  
**Short Internal Lug Adapter**  
 FEMALE NPT x MALE  
 † 1 1/2" x 1 1/2" (38 x 38 mm)  
 ✓† 2 1/2" x 2 1/2" (65 x 65 mm)  
 † 3" x 2 1/2" (75 x 65 mm)  
 † 3" x 3" (75 x 75 mm)



**337**  
**Rigid Female to Male Adapter**  
 † 3/4" GHT x 1" (19 x 25 mm)  
 † 1" x 3/4" GHT (25 x 19 mm)  
 † 1" x 1" (25 x 25 mm)  
 † 1" x 1 1/2" (25 x 38 mm)  
 † 1 1/4" x 1" (32 x 25 mm)  
 † 1 1/2" x 3/4" (38 x 19 mm)  
 † 1 1/2" x 1" (38 x 25 mm)  
 † 1 1/2" x 1 1/2" (38 x 38 mm)  
 † 1 1/2" x 2" (38 x 50 mm)  
 † 1 1/2" x 2 1/2" (38 x 65 mm)  
 † 2" x 1" (50 x 25 mm)  
 † 2" x 1 1/2" (50 x 38 mm)  
 † 2" x 2" (50 x 50 mm)  
 † 2" x 2 1/2" (50 x 65 mm)  
 † 2 1/2" x 3/4" GHT (65 x 19 mm)  
 † 2 1/2" x 1 1/2" (65 x 38 mm)  
 † 1 1/2" x 1" (38 x 25 mm)  
 \*† 2 1/2" x 1 1/2" (65 x 38 mm)  
 † 2 1/2" x 2" (65 x 50 mm)  
 † 2 1/2" x 2 1/2" (65 x 65 mm)  
 † 2 1/2" x 3" (65 x 76 mm)  
 † 2 1/2" x 3 1/2" (65 x 89 mm)  
 † 3" x 1 1/2" (75 x 38 mm)  
 † 3" x 2 1/2" (75 x 65 mm)  
 † 3" x 3" (75 x 75 mm)  
 † 3" x 3 1/2" (75 x 89 mm)  
 † 3 1/2" x 2 1/2" (89 x 65 mm)  
 † 3 1/2" x 3" (89 x 75 mm)



**356**  
**Rigid Female to Male Adapter**  
 † 2 1/2" x 4" (65 x 100 mm)  
 † 3 1/2" x 4" (89 x 100 mm)  
 † 4" x 2 1/2" (100 x 65 mm)  
 † 4" x 3" (100 x 75 mm)  
 † 4" x 3 1/2" (100 x 89 mm)  
 † 4" x 3" (100 x 75 mm)  
 † 4" x 3 1/2" (100 x 89 mm)  
 ✓† 4" x 4" (100 x 100 mm)  
 † 4" x 4 1/2" (100 x 114 mm)  
 † 4" x 5" (100 x 125 mm)  
 † 4" x 6" (100 x 153 mm)  
 † 4 1/2" x 2 1/2" (114 x 65 mm)  
 † 4 1/2" x 3" (114 x 75 mm)  
 † 4 1/2" x 4" (114 x 100 mm)  
 † 4 1/2" x 4 1/2" (114 x 114 mm)  
 † 4 1/2" x 5" (114 x 125 mm)  
 † 4 1/2" x 6" (114 x 150 mm)  
 † 5" x 2 1/2" (125 x 65 mm)  
 † 5" x 3" (125 x 75 mm)  
 † 5" x 4" (125 x 100 mm)  
 ✓† 5" x 4 1/2" (125 x 114 mm)  
 † 5" x 5" (125 x 125 mm)  
 † 5" x 6" (125 x 150 mm)  
 † 6" x 3" (150 x 75 mm)  
 † 6" x 4" (150 x 100 mm)  
 ✓† 6" x 4 1/2" (150 x 114 mm)  
 ✓† 6" x 5" (150 x 125 mm)  
 † 6" x 6" (150 x 150 mm)



**338**  
**Suction Lug Adapter with Strainer**  
 FEMALE NPT x FEMALE SWIVEL  
 † 1 1/2" x 1 1/2" (38 x 38 mm)  
 † 2 1/2" x 2 1/2" (65 x 65 mm)  
 † 3" x 2 1/2" (75 x 65 mm)  
 3" x 3" (75 x 75 mm)  
 3" x 3 1/2" (75 x 89 mm)  
 3 1/2" x 3 1/2" (89 x 89 mm)  
 3 1/2" x 4" (89 x 100 mm)  
 4" x 3 1/2" (100 x 89 mm)  
 † 4" x 4" (100 x 100 mm)



**361**  
**Double Male Hex Nipple**  
 # 3/4" x 3/4" (19 x 19 mm)  
 GHT or NPSH  
 # 1" x 3/4" GHT (25 x 19 mm)  
 † 1" x 1" (25 x 25 mm)  
 # 1 1/2" x 1" NH (38 x 25 mm)  
 † 1 1/2" x 1 1/2" (38 x 38 mm)  
 † 2" x 1 1/2" NH (50 x 38 mm)  
 † 2" x 2" (50 x 50 mm)  
 † 2 1/2" NH or (65 mm)  
 NPT, or NPSH  
 † 2 1/2" x 2 1/2" (65 x 65 mm)



**362**  
**Female to Male Hex Nipple**  
 † 3/4" NPT x 3/4" NH (19 x 19 mm)  
 or NPSH  
 † 3/4" GHT (19 mm)  
 † 1" x 3/4" GHT (25 x 19 mm)  
 † 1" x 1" (25 x 25 mm)  
 1 1/2" x 3/4" GHT (38 x 19 mm)  
 † 1 1/2" x 1 1/2" (38 x 38 mm)  
 † 2" x 1 1/2" (50 x 38 mm)  
 † 2" x 2 1/2" (50 x 65 mm)  
 † 2 1/2" x 2 1/2" (65 x 65 mm)  
 † 3" x 2 1/2" (75 x 65 mm)

- 631 60° Angle Elbow**
- For high-rise stand pipes
  - Pyrolite® finish
  - 2 1/2" female x 2 1/2" male
  - Weight: 1 7/8 lbs.

- 633 30° Discharge Elbow**
- For use on the pumper discharge
  - Chrome finish
  - 2 1/2" NPT X 2 1/2" NH weight: 3 lbs.

- 650 Swiveling Elbow**
- For aerial applications
  - Pyrolite finish
  - Full flow waterway with cast-in turning vanes for reduced friction loss
  - Available in 4", 5" and 6" sizes
  - Height 12 1/2"
  - Weight: 8 3/4 lbs.



Style 631



Style 650



Style 633