

## Clappered Siamese

- 262 Clapper Valve Siamese**  
A brass Clapper Siamese with a leather carrying handle and 3/4" drain plug.
- 266 Clapper Valve Siamese**  
A brass Clapper Siamese in sizes up to 6".
- 1256 3-Way Clapper Valve Siamese - Pyrolite®**  
Three 2 1/2" female inlets x 4" to 6" male or female outlet. Includes Style 4 Drainit drain valve and rubber carrying handle. Optional Pressure Gauge
- 1262 Clapper Valve Siamese**  
A Pyrolite Clapper Siamese includes a Style 4 Drainit drain valve and a rubber carrying handle.
- 1267 Clapper Valve Siamese**  
A Pyrolite Clapper Siamese includes a Style 4 Drainit drain valve and a rubber carrying handle.

Style	Material	Length	Width	Weight lbs. (kg)	Inlet	Outlet
262	Brass	7 3/4" (197 mm)	9" (229 mm)	14 1/2 (6.6 kg)	(2) 2 1/2" F (65 mm)	2 1/2" or 3" M (65 or 75 mm)
266	Brass	8" (203 mm)	9" (229 mm)	21 1/4 * (9.6 kg)	(2) 2 1/2" F (65 mm)	3" - 6" F (75 -150 mm)
1256	Pyrolite	12 3/4" (323 mm)	14 3/4" (375 mm)	15 1/2 (7 kg)	(3) 2 1/2" F (65 mm)	2 1/2" - 6" M or F (65-150 mm)
1262	Pyrolite	8 1/2" (216 mm)	9 3/8" (238 mm)	7 1/4 (3.3 kg)	(2) 2 1/2" F (65 mm)	2 1/2" or 3" M (65 or 75 mm)
1267	Pyrolite	9 3/8" (238 mm)	9 3/8" (238 mm)	9 1/2 (4.3 kg)	(2) 2 1/2" F (65 mm)	2 1/2" - 6" F, (65-150 mm) 3 1/2" - 6" M, 4" or 5" Storz (89-150, 100 or 125 mm)

\* Weight with 4 1/2" (114 mm) outlet



Style 266



Style 262



Style 1262



Style 1256



Style 1267